KBUC14125S46A

The model is high performance, low spurious and low phase noise Block Up-Converter. The model is the key component of the broadcast communication, satellite communication and radar system.

FEATURES:

- Integrated BUC for Better Performance & Reliability
- Monitoring & Controlling
- Tricolour LED Status Indicator to Identify BUC Status Instantly

Electrical specifications

Parameter		Specifications	
IF Frequency Range		950 ~1700 MHz	
Output Frequency Range		13.75~14.5 GHz	
LO Frequency		12.8 GHz	
Saturated Output Power		46 dBm (Min)	
Power Gain @ Pin=-20dBm		66 dB (Min)	
Power Gain Flatness		±1 dB (Typ)	
Small Signal Gain @Pin=-40dBm		76 dB (Typ)	
Small Signal Gain Flatness		±2 dB (Typ)	
IM3 @Pout = 39dBm (two tones, 5MHz)		-25 dBc (Max)	
Spurious		-55dBc (Typ)	
Gain control Range		20dB Variable, Step size of 0.25dB	
Phase Noise	100Hz	≤-63 dBc/Hz	
	1kHz	≤-73 dBc/Hz	
	10kHz	≤-83 dBc/Hz	
	100kHz	≤-93 dBc/Hz	
	1MHz	≤-103 dBc/Hz	
Input VSWR		1.5:1 (typ)	
Output VSWR		1.3:1 (Max)	
Input/Input Impedance		50 Ω	
External Reference Input		Frequency	10MHz
		Power	-5 to 5 dBm (Unit will automatically switch to internal reference if external reference level falls below -10 dBm nominal）
		Phase Noise	-135dBc/Hz@100Hz max. -145dBc/Hz@1kHz max. -155dBc/Hz@10kHz max.
M&C Function Interface		Ethernet (default) , optional RS485/232	
LED Function		Green: Normal, Red: Fault, Blue: PA Off	
Command Function		PA On/Off, Gain Control, Out-of-lock Alarm, Temperature, Over- VSWR Protection, Summary Alarm	

Focus on Your Application

Chengdu KeyLink Wireless Technology Co., Ltd.
>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China
>> Phone: +86(28)87870761*8708 >> Fax: +86(28)87883266
>> Email: sales@keylinkmw.com >> www.keylinkmw.com

Specifications subject to change without notice

KBUC14125S46A

Protection and Warning Function

No	Specifications
1	Unlock protection/ Warning
2	Over-current protection/ Warning
3	Over-voltage protection/ Warning
4	Over-temperature protection/ Warning
5	Over-reflection protection/ Warning

Interface

Tag	Specifications	Connector model
IF/ REF IN	IF/ REF input	N
RF OUT	Output	WR-75G
M&C	LAN	Circle Connector
Power DC 28V	Power supply	Circle Connector

Power DC Interface Connector (4pin Circle Connector)

PIN	Specifications	Connector model
1,2	28VDC	
3,4	GND	

Operating Power Requirement

Parameter	Specifications
Operating Voltage	24~30VDC, 28VDC (Typ)
Power Consumption	200 Watts (Typ)

Environmental Conditions

Parameter	Specifications
Operating Temperature	-40°C to +60°C
Storage Temperature	-50°C to +70°C
Humidity	0 to 95%
Water proof/ Dust proof	IP65

Mechanical

Parameter	Specifications
Dimensions (L x W x H)	150 x 100 x 90(mm)
Weight	3kg
Paint	RAL7035(GRAY)

Absolute Maximum Ratings

Parameter	Specifications
IF input power	≤5dBm
Load VSWR @RF OUT	VSWR≤5:1(assured by design)
Thermal Degradation	85℃ @ heatsink

Focus on Your Application

Chengdu KeyLink Wireless Technology Co., Ltd.
>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China
>> Phone: +86(28)87870761*8708 >> Fax: +86(28)87883266
>> Email: sales@keylinkmw.com >> www.keylinkmw.com

Specifications subject to change without notice